

DISSIDENT & FRINGE 2.0

Dissident / Fringe/ Sequel

*Milliken***SPECIFICATION**

| | |
|----------------------------------|---|
| Construction | Tufted, Textured Loop |
| Face Fiber | 100% Milliken-Certified Nylon |
| Tile Size | 50 cm x 50cm |
| Dye Method | Millitron® |
| Gauge | 1/12 |
| Stitches | 11.4 |
| Standard Backing | PVC-Free WellBAC® Comfort Available with TractionBack® |
| Recyclability | 100% |
| Recycled Content By Total Weight | 39.0%(36.4% Post Industrial and 2.6% post consumer) |
| Nominal Total Thickness | 10.3mm±10% |

PERFORMANCE

| | |
|--|---|
| Stain Resist / Soil Release | StainSmart® |
| Flammability (Radiant Panel ASTM-E-648) | ≥ 0.45 (Class I) |
| Smoke Density (NFPA-258-T or ASTM-E-662) | ≤ 450 |
| Methenamine Pill Test (CPSC FF-1-70 or ASTM D 2859) | Self-Extinguishing |
| Lightfastness (AATCC 16E) | ≥ 4.0 at 80 Hours |
| Crocking (AATCC 165) | ≥ 4.0 Wet or Dry |
| Static Electricity (AATCC-134) 20% R.H., 70° F. | ≤ 3.5 KV, Permanent Conductive Fiber |
| Texture Appearance Retention Rating (TARR) | Severe |
| Indoor Air Quality—CRI Green Label Plus™ | GLP3237, Carpet Category 5Y |

WARRANTIES

| |
|---|
| Lifetime Face Fiber Wear |
| Lifetime Antistatic |
| Lifetime Floor Compatibility |
| Lifetime Color Pattern Permanency |
| Lifetime Floor Release |
| Lifetime Cushion Resiliency |
| Lifetime Moisture Resistance |
| Lifetime Delamination of Backing |
| Lifetime Dimensional Stability |
| Lifetime Tuft Bind |
| Lifetime Edge Ravel |
| Lifetime Flammability |
| Lifetime Staining/Soiling (StainSmart®) |

INSTALLATION METHOD

Monolithic
For Sequel only



Ashlar

3RD PARTY CERTIFICATES

Declare.

Design Copyright – Milliken & Company. This carpet tile product is covered by one or more patents, published applications and / or patents pending. Specifications are subject to normal manufacturing tolerances and may be changed without prior notice. Copies of actual test results are available upon request.