

Gentle Ground- Grounded Suede, Grounded Contours

FlexForm™ LVT

Milliken™

SPECIFICATION

| | |
|----------------------|---|
| Construction | High Performance Flex Form LVT |
| Finish | ProGuard™ Reinforced Polyurethane Coating |
| Overall Thickness | 5mm |
| Wear Layer Thickness | 0.55mm |
| Edge Profile | Micro Bevel |
| Tile Sizes | 25cmX100cm |
| Pieces Per Box | 8 |
| Weight Per Box | 19.6kg |
| Quantity Per Box | 2 m ² |

PERFORMANCE

| | |
|--|---------------------------|
| Critical Radiant Flux (ISO 9239-1) | ≥4.5kW/m ² |
| Smoke Rate(ISO 9239-1) | <750%.min |
| Use Classification (ISO 10582) | Class 33 Heavy Commercial |
| Colour Fastness to Light (ISO 105-B02) | ≥6 |
| Slip Resistance (DIN 51130) | R10 |
| Dimensional Stability (ISO 23999) | ≤0.25 % ; Curl ≤2 mm |
| Resistance to Chemicals (ISO26987) | Pass |
| Residual Indentation (ISO 24343-1) | ≤0.1 mm |
| Castor Chair Resistance (ISO 4918) | Pass |
| Flexibility(ISO 24344) | Pass |

WARRANTIES

15-Year Limited Commercial Wear

Installation

Glue Down

3RD PARTY CERTIFICATES

Declare.



Milliken LVT is highly durable resilient flooring engineered with the highest quality raw materials to provide unsurpassed performance and enduring aesthetics. Milliken LVT is 100% ortho-phthalate-free. Milliken LVT is manufactured at facilities that are ISO 9001 and ISO 14001 compliant. Specifications are subject to normal manufacturing tolerances and may be changed without prior notice. Images in this brochure are approximate for color and pattern scale. Please use actual product samples to make your final selections.