

# PATTERN PLAY



SPECIFICATION	
Construction	Tufted Textured Loop
Face Fiber	100% Milliken-Certified Nylon
Tile Size	50cmx50cm
Dye Method	Millitron®
Gauge	1/10
Stitches	14
Standard Backing	PVC-Free WellBAC® Comfort Available with TractionBack®
Recyclability	100%
Recycled Content By Total Weight	45% (42% Post Industrial, 3% Post Consumer)
Nominal Total Thickness	8.4mm±10%
PERFORMANCE	
Stain Resist / Soil Release	StainSmart®
Flammability (Radiant Panel ASTM-E-648)	≥ 0.45 (Class I)
Smoke Density (NFPA-258-T or ASTM-E-662)	≤ 450
Methenamine Pill Test (CPSC FF-1-70 or ASTM D 2859)	Self-Extinguishing
Lightfastness (AATCC 16E)	≥ 4.0 at 80 Hours
Crocking (AATCC 165)	≥ 4.0 Wet or Dry
Static Electricity (AATCC-134) 20% R.H., 70° F.	≤ 3.5 KV, Permanent Conductive Fiber
Texture Appearance Retention Rating (TARR)	Severe
Indoor Air Quality—CRI Green Label Plus™	Pass
WARRANTIES	
Lifetime Face Fiber Wear	
Lifetime Antistatic	
Lifetime Floor Compatibility	
Lifetime Color Pattern Permanency	
Lifetime Floor Release	
Lifetime Flammability	
Lifetime Moisture Resistance	
Lifetime Delamination of Backing	
Lifetime Dimensional Stability	
Lifetime Tuft Bind	
Lifetime Edge Ravel	
Lifetime Cushion Resiliency	
Lifetime Staining/Soiling (StainSmart®)	
INSTALLATION METHOD	
Monolithic	Ashlar
V. Ashlar	



Monolithic      Ashlar      V. Ashlar



**Design Copyright – Milliken & Company.** This carpet tile product is covered by one or more patents, published applications and / or patents pending. Specifications are subject to normal manufacturing tolerances and may be changed without prior notice. Copies of actual test results are available upon request.