

MOMENTS IN TIME

Understory/Crossweave/Woven Horizon/Afterglow

SPECIFICATION	
Construction	Tufted Textured Loop
Face Fiber	100% Milliken-Certified Nylon
Tile Size	50cmx50cm
Dye Method	Millitron®
Gauge	1/10
Stitches	14
Standard Backing	PVC-Free WellBAC® Comfort Available with TractionBack®
Recyclability	100%
Recycled Content By Total Weight	45% (42% Post Industrial, 3% Post Consumer)
Nominal Total Thickness	8.4mm±10%

PERFORMANCE		WARRANTIES
Stain Resist / Soil Release	StainSmart®	Lifetime Face Fiber Wear
Flammability (Radiant Panel ASTM-E-648)	≥ 0.45 (Class I)	Lifetime Antistatic
Smoke Density (NFPA-258-T or ASTM-E-662)	≤ 450	Lifetime Floor Compatibility
Methenamine Pill Test (CPSC FF-1-70 or ASTM D 2859)	Self-Extinguishing	Lifetime Color Pattern Permanency
Lightfastness (AATCC 16E)	≥ 4.0 at 80 Hours	Lifetime Floor Release
Crocking (AATCC 165)	≥ 4.0 Wet or Dry	Lifetime Flammability
Static Electricity (AATCC-134) 20% R.H., 70° F.	≤ 3.5 KV, Permanent Conductive Fiber	Lifetime Moisture Resistance
Texture Appearance Retention Rating (TARR)	Severe	Lifetime Delamination of Backing
Indoor Air Quality—CRI Green Label Plus™	Pass	Lifetime Dimensional Stability
		Lifetime Tuft Bind
		Lifetime Edge Ravel
		Lifetime Cushion Resiliency
		Lifetime Staining/Soiling (StainSmart®)

INSTALLATION METHOD



Monolithic

Ashlar

V. Ashlar



Design Copyright – Milliken & Company. This carpet tile product is covered by one or more patents, published applications and / or patents pending. Specifications are subject to normal manufacturing tolerances and may be changed without prior notice. Copies of actual test results are available upon request.